


## HIGH CAPACITY FILTRATION WITH MINIMUM SPACE REQUIREMENTS

### 450 GPM CAPACITY

- SKID: 5'W x 5'L x 7'H
- WEIGHT: 850 Pounds
- 316 Stainless Steel
- 340 PSI ASME Code
- 6" PIPING




# The Cost Effective Approach to Quality Filtration

**FTC introduces its new 2040 PLATINUM Series absolute rated filter cartridge.**

This unique design, U.S. Patent No. 5824232, uses segregated flow channels and flow chambers to maximize the effective surface area of the pleated filter media within a 20.0 inch OD cartridge. Combining this design with the technique of pleating several different filter media together in a single pleat pack maximizes dirt holding capacity.


One 2040 PLATINUM Series filter is designed to have the dirt holding capacity of 600 string wound or 150 standard 2.5 inch OD pleated cartridges of similar length. Available in a wide variety of filter media, this cartridge is constructed with metal end caps and core for high temperature applications.

With a recommended flow rate up to 450 GPM, this FTC PLATINUM Series system is the solution to achieving optimum performance while minimizing filtration costs.



## DIRT HOLDING CAPACITY

DATA FOR 2040 SERIES



Notice: The information presented here is based on tests and data which FTC believes to be reliable, but their accuracy or completeness is not guaranteed. FTC MAKES NO WARRANTIES, EXPRESS OR IMPLIED, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The determination of whether the FTC product is fit for a particular purpose or application is the responsibility of the user.



5175 Ashley Court  
Houston, TX. 77041  
Tel: (713) 849-0849  
Fax: (713) 849-0202  
[www.ftc-houston.com](http://www.ftc-houston.com)